

SAFETY DATA SHEET SILVER STAR

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME SUPPLIER SILVER STAR

ARDEX ENDURA (INDIA) PRIVATE LIMITED Corporate Office & Regd. Office: Unit No. 406 & 407, "Brigade Rubix", No. 20, Yeshwanthapur Hobli, HMT Campus, Bangalore - 560022. Karnataka, INDIA. CIN No: U24233KA1997PTC022383 Tel: +91 80 66746500 Fax: +91 80 66746540 Email: customercare@ardexendura.com Visit us: www.ardexendura.com

2. HAZARDS IDENTIFICATION

Risk of serious damage to eyes.

CLASSIFICATION (1999/45) Xi;R41.

HUMAN HEALTH

When the cement based powder is mixed with water, a strongly alkaline paste is produced. Cement based products may, until set, cause both irritant and allergic contact dermatitis. Irritrant contact dermatitis is due to a combination of the wetness, alkalinity and abrasiveness of the constituent materials. Allergic contact dermatitis is caused mainly by the sensitivity of the individual's skin to hexavalent chromium salts.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS-No.	Content	Classification (67/548/EEC)
ORDINARY PORTLAND CEMENT	65997-15-1	40-50%	Xi;R41.
GRADED FILLER		50-60%	
POLYMER		05-10%	

The Full Text for all R-Phrases is Displayed in Section 16

COMPOSITION COMMENTS

The grey adhesives contain a reducing agent to ensure that the CrVI content of the adhesive remains below 2ppm during the defined shelf life of the adhesive.

4. FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT induce vomiting. Get medical attention immediately. Immediately rinse mouth and drink plenty of water (200-300 ml).

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention immediately. Continue to rinse.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

The product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SILVER STAR

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Avoid contact with skin or inhalation of spillage, dust or vapour. Dampen spillage with water. Absorb in vermiculite, dry sand or earth and place into containers. Shovel into dry containers. Cover and move the containers. Flush the area with water.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid contact with skin and eyes. Provide good ventilation.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place.

STORAGE CLASS Chemical storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ORDINARY PORTLAND CEMENT	WEL	4	4 mg/m3			

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION Use protective gloves.

EYE PROTECTION Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Promptly remove any clothing that becomes contaminated.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Powder, dust.

10. STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID Avoid contact with acids.

HAZARDOUS DECOMPOSITION PRODUCTS Fire creates: Carbon monoxide (CO). Carbon dioxide (Co2).

11. TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system. May cause damage to mucous membranes in nose, throat, lungs and bronchial system. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

INGESTION

Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

SKIN CONTACT

The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

EYE CONTACT

Risk of serious damage to eyes. May cause chemical eye burns.

HEALTH WARNINGS

Repeated exposure in excess of the WEL has been linked with rhinitis and coughing. Skin exposure has been linked to allergic chromium dermatitis.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.

MOBILITY

The product is non-volatile. The product is insoluble in water and will sediment in water systems.

BIOACCUMULATION

No data available on bioaccumulation.

13. DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Dispose of waste and residue in accordance with local authority requirements.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG IATA, ADR/RID).		
No transport warning sign required.		
Not Classified		
Not classified.		
Not classified.		
Not classified.		

15. REGULATORY INFORMATION

LABELLING



SILVER STAR

R41 Risk of serious damage to eyes.	RISK PHRASES	
SAFETY PHRASES	R41	Risk of serious damage to eyes.
SALETT THINKED	SAFETY PHRASES	
S2 Keep out of the reach of children.	S2	Keep out of the reach of children.
S24/25 Avoid contact with skin and eyes.	S24/25	Avoid contact with skin and eyes.
\$36/37/39 Wear suitable protective clothing, gloves and eye/face protection.	\$36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
P17 Contains chromium (VI). May produce an allergic reaction.	P17	Contains chromium (VI). May produce an allergic reaction.
P31 Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.	P31	Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.
P32 Contact between cement powder and body fluids (eg. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.	P32	

STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16. OTHER INFORMATION

 TRAINING ADVICE
 :
 The details of this data sheet must be passed on to all personnel handling the product.

RISK PHRASES IN FULL

R41 Risk of serious damage to eyes.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.