



SAFETY DATA SHEET

WPM 004 Flex Part B

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME WPM 004 Flex Part B

SUPPLIER ARDEX ENDURA (INDIA) PRIVATE LIMITED
Corporate Office & Regd. Office:
Unit No. 406 & 407, "Brigade Rubix", No. 20, Yeshwanthapur Hobli,
HMT Campus, Bangalore - 560022. Karnataka, INDIA.
CIN No: U24233KA1997PTC022383
Tel: +91 80 66746500
Email: customercare@ardexendura.com Visit us: www.ardexendura.com

PRODUCT USE High Performance Acrylic Reinforced Waterproof Coating

DATE 25/05/2020

2. HAZARDS IDENTIFICATION

HUMAN HEALTH

When the cement based powder is mixed with water or admixture, a strongly alkaline paste is produced. Cement based products may, until set, cause both irritant and allergic contact dermatitis. Irritant contact dermatitis is due to a combination of the wetness, alkalinity and abrasiveness of the constituent materials. Allergic contact dermatitis is caused mainly by the sensitivity of the individual's skin to hexavalent chromium salts.

Risk of serious damage to eyes

Label elements

Pictogram:



3. COMPOSITION / INFORMATION ON INGREDIENTS

Names	CAS No.	Other Information	Concentration
Ordinary Portland Cement	65997-16- 2	NA	40 – 60%
Graded Mineral Fillers	NA	NA	25 – 45%

The Full Text for all R-Phrases are Displayed in Section 16.

4. FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention immediately. Continue to rinse.

WPM 004 Flex Part B

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

UNUSUAL FIRE & EXPLOSION HAZARDS

May form explosive mixture with air at very high concentration.

SPECIFIC HAZARDS

In case of fire, toxic gases may be formed. Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Avoid contact with skin or inhalation of spillage, dust or vapour. Dampen spillage with water. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer. Shovel into dry containers. Cover and move the containers. Flush the area with water.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in dry and cool place

STORAGE CLASS

Chemical storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
Ordinary Portland Cement	WEL		4 mg/m ³			

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT

PROCESS CONDITIONS: Provide eyewash station.



ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

WPM 004 Flex Part B**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical State	: Powder, dust
Colour	: Grey
Odour	: Odour less
Boiling Point/Range (C)	: NA
Flash Point (Closed, C)	: NA
Autoflammability (C)	: NA
Oxidising Properties	: NA
Relative Density (at 20 C)	: NA
Water Solubility	: Insoluble
pH (working dilution)	: 13

10. CHEMICAL STABILITY AND REACTIVITY INFORMATION**STABILITY**

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (Co2) Nitrous gases (NOx).

11. TOXICOLOGICAL INFORMATION**INHALATION**

May cause irritation to the respiratory system. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

Harmful

Danger of serious damage to health by prolonged exposure through inhalation.

INGESTION

Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

SKIN CONTACT

The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact.

EYE CONTACT

Risk of serious damage to eyes. May cause chemical eye burns.

HEALTH WARNINGS

Repeated exposure in excess of the WEL has been linked with rhinitis and coughing. Skin exposure has been linked to allergic chromium dermatitis

12. ECOLOGICAL INFORMATION**ECOTOXICITY**

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms.

MOBILITY

The product is non-volatile. The product is insoluble in water and will sediment in water systems.

BIOACCUMULATION

No data available on bioaccumulation

13. DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION**GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

WPM 004 Flex Part B

ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not Classified.
SEA TRANSPORT NOTES	Not Classified.
AIR TRANSPORT NOTES	Not Classified.

15. REGULATORY INFORMATION

RISK PHRASES	Risk of serious damage to eyes.
SAFETY PHRASES	Keep out of the reach of children Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection. Contains chromium (VI). May produce an allergic reaction. Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns. Contact between cement powder and body fluids (eg. sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns
STATUTORY INSTRUMENTS	Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE	Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES	Workplace Exposure Limits EH40. CHIP for everyone HSG (108).

16. OTHER INFORMATION

TRAINING ADVICE	The details of this data sheet must be passed on to all personnel handling the product.	
RISK PHRASES IN FULL	R38	Irritating to skin.
	R41	Risk of serious damage to eyes.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.