



SAFETY DATA SHEET

B 51 PART A

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME B 51 PART A

SUPPLIER **ARDEX ENDURA (INDIA) PRIVATE LIMITED**
 Corporate Office & Regd. Office:
 Unit No. 406 & 407, Brigade Rubix, No. 20, Yeshwanthapur Hobli,
 HMT Campus, Bangalore - 560022, Karnataka, INDIA.
 CIN No: U24233KA1997PTC022383
 Tel: +91 80 66746500 Fax: +91 80 66746540
 Email: customercare@ardexendura.com Visit us: www.ardexendura.com

2. HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
epoxy resin		55492-52-9	10-30 %	Xi;R36/38. N;R51/53. R43.
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	60-100 %	R43 Xi;R36/38 N;R51/53
OXIRANE, MONO [(C12-14- ALKYL OXY)METHYL] DERIVS		68609-97-2	10-30 %	R43 Xi;R38
Alkyl Phenol Blocked Polyisocyanate		Trade Secret	95-100 %	
Phenol, nonyl-, branched		84852-15-3	1-5 %	

The Full Text for all R-Phrases are Displayed in Section 16

4. FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

B 51 PART A**6. ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7. HANDLING AND STORAGE**USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT**PROCESS CONDITIONS**

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use protective gloves made of: Nitrile. Viton rubber (fluor rubber). Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

EYE PROTECTION

Wear tight-fitting goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE**

Liquid

ODOUR

Characteristic

SOLUBILITY

Immiscible with water.

B 51 PART A

10. STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

INHALATION

Irritating to respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

May cause sensitisation by skin contact. Irritating to skin.

EYE CONTACT

Irritating to eyes.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION



UK ROAD CLASS	9		
PROPER SHIPPING NAME	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700), epoxy resin)		
UN NO. ROAD	3082	UK ROAD PACK GR.	III
ADR CLASS NO.	9	ADR CLASS	Class 9: Miscellaneous dangerous substances and articles.
ADR PACK GROUP	III	HAZARD No. (ADR)	90
ADR LABEL NO.	9	HAZCHEM CODE	3Z
CEFIC TEC(R) NO.	90GM6-III	RID CLASS NO.	9
RID PACK GROUP	III	UN NO. SEA	3082
IMDG CLASS	9	IMDG PACK GR.	III
EMS	F-A,S-F	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	3082
AIR CLASS	9	AIR PACK GR.	III

B 51 PART A**15. REGULATORY INFORMATION**

LABELLING



Irritant



Dangerous for the environment

CONTAINS

Epoxy resin

EPOXY RESIN (Number average MW $\leq$ 700)

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

RISK PHRASES

R43 May cause sensitisation by skin contact.

R36/38 Irritating to eyes and skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S37 Wear suitable gloves.

S24/25 Avoid contact with skin and eyes.

S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

P5 Contains epoxy constituents. See information supplied by the manufacturer.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH 40. CHIP for everyone HSG(108).

16. OTHER INFORMATION

TRAINING ADVICE : The details of this data sheet must be passed on to all personnel handling the product.

RISK PHRASES IN FULL

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.