



FOR GOOD REASONS

---

# panDOMO<sup>®</sup> PF

## Maintenance Oil

---

For the care of those areas subject to heavy wear on sanded surfaces of PANDOMO Floors and those treated with PANDOMO SL Stone oil

Oil-based, free from preservatives

Penetrating, not layer forming

Breathable

Biologically degradable



Reg. No. 37344

Manufacturer  
with certified quality system  
as per DIN EN ISO 9001

ARDEX GmbH  
58430 Witten · P.O. Box 61 20  
GERMANY  
Telephone: +49 (0) 23 02/664-0  
Telefax: +49 (0) 23 02/664-437  
kundendienst@ardex.de  
www.ardex.de

# panDOMO<sup>®</sup> PF

## Maintenance Oil

---

### Applications:

#### For inside use.

PANDOMO PF Maintenance oil enhances the care of those surfaces treated with PANDOMO SL Stone oil which are subject to particularly heavy wear, e.g. entrance areas, contact surfaces, door openings and many others.

### Type:

PANDOMO PF Maintenance oil is an oil-based product.

The surface structure of surfaces treated with PANDONO SL Stone oil is not altered.

### Use:

Apply PANDOMO PF Maintenance oil finely from a spray bottle or with a fluff-free cloth in a thin layer to the surface to be treated. Leave to soak in for approx. 10 mins., then rub in, using a white or beige pad until it is dry. Ensure that after this has been done no moist film of oil or oil splashes remain on the surface!

If dull, worn areas appear or the odd patch shows up, simply re-oil the offending places with PANDOMP PF Maintenance oil (e.g. with a fluff-free cloth).

### N.B.:

Ensure good movement of air close to the floor (open Doors).

Temperatures from +18°C and above will accelerate the drying process. The drying time must be at least 6 hours.

Do not walk on the floor until no more traces of the applied oil are visible.

During this period protect against water!

To permanently preserve the value of the finished floor, be sure to follow our maintenance instructions.

### Cleaning and disposal:

After use tools must be thoroughly cleaned with a brush cleaner or turps substitute. Instructions on disposal are contained in the EC safety data sheet.

### Note:

PANDOMO PF Maintenance oil is physiologically harmless in the cured state.

Ensure good ventilation. If product comes into contact with eyes, rinse immediately with clear water.

Do not work with naked flames.

The dried coat is not flammable.

### Technical data

#### according to ARDEX quality standards:

---

**Density:** approx. 0.9 kg/l

**Consumption:** approx. 25 g/m<sup>2</sup>

**Supplied as:** 1 l tins

**Storage:** can be stored in a dry environment in well sealed containers for 12 months

---

We assume the warranty for the perfect quality of our products. Our handling recommendations are based on trials and practical experience; they can, however, only be regarded as general advice without a quality warranty, as we have no influence on work site conditions and the execution of the work.  
Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations.