

Material Safety Data Sheet R 25 CE Part B

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME R 25 CE PART B

SUPPLIER ARDEX ENDURA (INDIA) PRIVATE LIMITED Corporate Office & Regd. Office: Unit No. 406 & 407, "Brigade Rubix", No. 20, Yeshwanthapur Hobli, HMT Campus, Bangalore - 560022. Karnataka, INDIA. CIN No: U24233KA1997PTC022383 Tel: +91 80 66746500 Fax: +91 80 66746540 Email: customercare@ardexendura.com Visit us: www.ardexendura.com

2. HAZARDS IDENTIFICATION

Causes burns. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful by inhalation and if swallowed.

CLASSIFICATION Xn;R20/22. C;R34. R43. R52/53.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BENZYL ALCOHOL	202-859-9	100-51-6	30-60%	Xn;R20/22
ISOPHORONEDIAMINE	220-666-8	2855-13-2	10-30%	C;R34 Xn;R21/22 R43 R52/53
m-PHENYLENEBIS(METHYLAMINE)	216-032-5	1477-55-0	10-30%	Xn;R20/22. C;R34. R43,R52/53.
SALICYLIC ACID	200-712-3	69-72-7	10-30%	Xn;R22. Xi;R41.

The Full Text for all R-Phrases are Displayed in Section 16

4. FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

SKIN CONTACT

Remove affected person from source of contamination. Promptly flush contaminated skin with soap or mild detergent and water. Promptly remove clothing if penetrated and flush the skin with water. Get medical attention if irritation persists after washing.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

UNUSUAL FIRE & EXPLOSION HAZARDS Fire causes formation of toxic gases.

SPECIFIC HAZARDS

By fire, toxic gases may be formed (COx, NOx).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Avoid discharge onto the ground.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Do not let washing down water contaminate ponds or waterways.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS Provide good ventilation.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS Chemical storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS Provide eyewash station.

ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided. Use chemical cartridge protection with appropriate cartridge.

HAND PROTECTION

Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

EYE PROTECTION Wear tight-fitting goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES				
APPEARANCE	Liquid			
COLOUR	Yellowish			
ODOUR	Amine			
SOLUBILITY	Immiscible with water			
BOILING POINT (°C)	>200 760 mm Hg	RELATIVE DENSITY	1.02 20	
VAPOUR PRESSURE	0.1 mbar 20	VISCOSITY	200 mPas 20	
FLASH POINT (°C)	>100 CC (Closed cup).	AUTO IGNITION	380	
		TEMPERATURE (°C)		
FLAMMABILITY LIMIT - LOWER(%)	1.2	Flammability Limit - Upper(%)	13.0	
VOLATILE ORGANIC COMPOUND	0			
VOC	655g/L			

10. STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID Avoid contact with strong oxidisers.

HAZARDOUS POLYMERISATION Will not polymerise.

MATERIALS TO AVOID Strong oxidising substances. Strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS By fire, toxic gases (CO, CO2, NOx) may be formed.

11. TOXICOLOGICAL INFORMATION

INHALATION

Harmful by inhalation. May cause sensitisation by inhalation. May cause respiratory allergy.

INGESTION

Harmful if swallowed. May cause chemical burns in mouth and throat.

SKIN CONTACT

Causes burns. May cause allergic contact eczema. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause sensitisation by skin contact.

EYE CONTACT

Causes burns. Extreme irritation of eyes and mucous membranes, including burning and tearing.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

WATER HAZARD CLASSIFICATION WGK 2

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14. TRANSPORT INFORMATION



UK ROAD CLASS	8			
PROPER SHIPPING NAME	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S			
	(ISOPHORONEDIAMINE, m-PHENYLENEBIS(METHYLAMINE)			
UN NO. ROAD	2735	UK ROAD PACK GR.	III	
ADR CLASS NO.	8	ADR CLASS	Class 8: Corrosive substances.	
ADR PACK GROUP	III	HAZARD NO. (ADR)	80	
ADR LABEL NO.	8	HAZCHEM CODE	2X	
CEFIC TEC(R) NO.	80GC7-II+III	RID CLASS NO.	8	
RID PACK GROUP	Ш	UN NO. SEA	2735	
IMDG CLASS	8	IMDG PACK GR.	III	
EMS	F-A, S-B	MARINE POLLUTANT	No.	
UN NO. AIR	2735	AIR CLASS	8	
AIR PACK GR.	III			

15. REGULATORY INFORMATION		
LABELLING	Ite II	×
	Corrosive	Harmful
CONTAINS		
RISK PHRASES	R34	Causes burns.
	R43	May cause sensitisation by skin contact.
	R52/53 R20/22	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful by inhalation and if swallowed.
SAFETY PHRASES	S26 S36/37/39	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection.
	S45	In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).
	S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
	S28	After contact with skin, wash immediately with plenty of water.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES Workplace Exposure Limits EH40.

16. OTHER INFORMATION

TRAINING ADVICE : The details of this data sheet must be passed on to all personnel handling the product. **RISK PHRASES IN FULL** R20/22 Harmful by inhalation and if swallowed. R21/22 Harmful in contact with skin and if swallowed. R22 Harmful if swallowed. R34 Causes burns. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.