

Material Safety Data Sheet R 21 CE Matt Part A

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME R 21 CE Matt PART A

SUPPLIER ARDEX ENDURA (INDIA) PRIVATE LIMITED

Corporate Office & Regd. Office:

Unit No. 406 & 407, "Brigade Rubix", No. 20, HMT Campus, Yeshwanthapur Hobli, Bengaluru - 560013. Karnataka, INDIA.

CIN No: U24233KA1997PTC022383

Tel: +91 80 66746500

Email: customercare@ardexendura.com Visit us: www.ardexendura.com

2. HAZARDS IDENTIFICATION

May cause sensitisation by skin contact. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Bisphenol F epichlorhydrin resin with MW <700		28064-14-4	1-5%	Xi;R36/38. N;R51/53. R43.
Epoxy resin		55492-52-9	10-25%	Xi;R36/38. N;R51/53. R43.
Filler	-	-	< 5%	-
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	30-60%	R43 Xi;R36/38 N;R51/53
LEVELLING ADDITIVE			< 1%	Xn;R65. Xi;R36/37. N;R51/53. R10.
N-METHYL-2-PYRROLIDONE	212-828-1	872-50-4	< 1%	Xi;R36/38
OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS		68609-97-2	5-10%	R43 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

4. FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

R 21 CE^{Flus} Matt Part A

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
N-METHYL-2-PYRROLIDONE	WEL	25 ppm(Sk)	103 mg/m3(Sk)	75 ppm(Sk)	309 mg/m3(Sk)

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT





PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use protective gloves made of: Nitrile. Viton rubber (fluor rubber). Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

EYE PROTECTION

Wear tight-fitting goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

R 21 CE Matt Part A

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid

COLOUR Clear Liquid

ODOUR CHARACTERISTICS
SOLUBILITY Immiscible with water

BOILING POINT (°C) >100 760 mm Hg DECOMPOSITION TEMPERATURE >200 (°C)

FLASH POINT (°C) 130 CC (Closed cup)

VOC 31.13 g/L

10. STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with acids and alkalies.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

INHALATION

Irritating to respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

May cause sensitisation by skin contact. Irritating to skin.

EYE CONTACT

May cause severe irritation to eyes.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

R 21 CE Matt Part A

14. TRANSPORT INFORMATION



UK ROAD CLASS 9

PROPER SHIPPING NAME ENVIRONMENT HAZARDOUS SUBSTANCE, LIQUID, N.O.S (EPOXY RESIN (Number average

 $MW \le 700$), epoxy resin)

UN NO. ROAD 3082 UK ROAD PACK GR. II

ADR CLASS NO. 9 ADR CLASS Class 9: Miscellaneous

dangerous substances and articles.

ADR PACK GROUP Ш HAZARD NO. (ADR) 90 ADR LABEL NO. HAZCHEM CODE 3Z CEFIC TEC(R) NO. 90GM6-III RID CLASS NO. 9 RID PACK GROUP Ш 3082 UN No. SEA IMDG PACK GR. **IMDG CLASS** 9 Ш F-A. S-F MARINE POLLUTANT **EMS** No. UN NO. AIR 3082 AIR CLASS 9

AIR PACK GR.

15. REGULATORY INFORMATION

LABELLING





Irritant

Dangerous for the environment

CONTAINS Bisphenol F epichlorhydrin resin with MW <700

epoxy resin

EPOXY RESIN (Number average MW <= 700)

OXIRANE, MONO [(C12-14- ALKYLOXY)METHYL] DERIVS

RISK PHRASES R43 May cause sensitisation by skin contact.

R36/38 Irritating to eyes and skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37 Wear suitable gloves.

S24/25 Avoid contact with skin and eyes.

S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

P5 Contains epoxy constituents. See information supplied by the manufacturer.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

REVISION DATE: 01/12/2022

R 21 CE Matt Part A

16. OTHER INFORMATION

TRAINING ADVICE : The details of this data sheet must be passed on to all personnel handling the product.

RISK PHRASES IN FULL

R10 Flammable.

R36/37 Irritating to eyes and respiratory system.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.