



# WPM 265

## Sheltercoat water based primer

### DESCRIPTION

WPM 265 is an acrylic primer system which creates a positive bond between the substrate and most water based coatings. WPM 265 can be used in internal as well as external applications.

### USES

As a primer for acrylic coatings in areas such as

- Internal Wet Areas
- Balconies and Decks
- Swimming Pools
- Drywalls
- Other waterproofing areas that will be tiled or otherwise protected from regular foot traffic

### FEATURES

- Creates a positive bond between the substrate and most water based coatings
- Can be used on various substrates
- Can be used for interior and external situations.

### SUITABLE SUBSTRATES:

- New and old concrete.
- Timber.
- Compressed fibreboards.

### PHYSICAL PROPERTIES

WPM 265	27 ± 1°C
Appearance	White/pink coloured liquid
Specific gravity	1.0 - 1.1 g/cc
Drying Time	Approx. 2 hours
Bond strength	> 1.5 N/mm <sup>2</sup>
VOC content	11 g/L

### COVERAGE ESTIMATES

<b>Pack size</b>	<b>Coverage</b>
5 litres	Approx. 6 m <sup>2</sup> /litre

**Note:** Coverage rate may vary depending on the porosity of the surface.

### APPLICATION INSTRUCTIONS

#### Substrate preparation

The surface to be treated must be dry, clean, structurally sound, free from oil, grease, wax, polish, laitance, dust and other barrier materials. New substrate shall be allowed to cure as per standard procedure

All cracks, construction joints, pipe penetration, bore packing and corners shall be treated prior to application of waterproofing membrane.

### Application

Stir the entire contents of WPM 265. Using a brush or long nap roller, apply uniformly on the prepared substrate include all construction joints, pipe penetration, bore packing and corners. Allow a drying time of at least 2 hours.

### Do's & Don'ts of WPM 265

- Do not apply WPM 265 if the temperature is below 10°C or above 35°C.
- Primed surfaces should preferably be overcoated within the same day of application to avoid intercoat contamination.

### CLEANING

Wash hands, brushes, rollers, etc with water while the material is still fresh. Remove cured material mechanically.

### STORAGE AND SHELF LIFE

WPM 265 has a shelf life of 12 months if kept in a dry, clean store between 5°C and 30°C in the original unopened containers. The product should be protected from frost, away from direct sunlight and sources of heat.

### SAFETY PRECAUTIONS

WPM 265 is non-toxic. Avoid contact with skin and inhalation of the vapour. Wear protective eye/face protection and gloves when handling. Provide adequate ventilation. Wash off splashes with clean water. If irritation persists, seek medical advice.

### DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Indian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program.

Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations.

The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

# WPM 265

Sheltercoat water based primer

---

## ARDEX ENDURA (INDIA) PRIVATE LIMITED

an **ISO 9001:2008** certified company  
Corporate Office & Regd. Office: Unit No. 406 & 407,  
"Brigade Rubix" No. 20, HMT Campus,  
Yeshwantpur Hobli, Bengaluru - 560013.  
CIN No: U24233KA1997PTC022383 Tel: +91 80 66746500  
Email: [customercare@ardexendura.com](mailto:customercare@ardexendura.com)  
Website: [www.ardexendura.com](http://www.ardexendura.com)

## Branches

• AHMEDABAD	079 26425310	• HUBBALLI	0836 2970505	• PATNA	+919934687909
• AURANGABAD	+918888480847	• HYDERABAD	040 27650293	• PUNE	020 64781879
• BENGALURU	080 40912934	• INDORE	0731 4021148	• RAIPUR	0771 6539055
• BHUBANESHWAR	0674 2421901	• JAIPUR	0141 2392993	• SALEM	0427 2211454
• CALICUT	0495 2740334	• KOLKATA	033 65090604	• SHIVAMOGGA	+919880605770
• CHENNAI	044 42805544	• LUCKNOW	0522 4043251	• TRICHY	0431 6454649
• DELHI	011 26802949	• LUDHIANA	0161 2532170	• TRIVANDRUM	0471 2558648
• ERNAKULAM	0484 2341044	• MANGALURU	0824 2442176	• VIJAYAWADA	+918688354587
• GHAZIABAD	0120 6541564	• MUMBAI	022 65133299	• VISAKAPATNAM	0891 6469499
• GOA	0832 2750992	• MYSURU	0821 2570171		
• GUWAHATI	+917896002188	• NAGPUR	+919822223743		

