



AC 20

Anti-Carbonation Facade Protective Coating

DESCRIPTION

AC 20 is an extremely weather resistant water based acrylic anti carbonation protective coating. The high build breathable coating exhibits excellent resistance to attack by carbon oxide, air borne chlorides and acid rain.

USES

Protection of concrete and masonry of

- Buildings and structures in coastal areas
- Marine or offshore structures such as jetties and berths
- External facade in chemical manufacturing plants, fertilizer manufacturing plants, power plants
- Bridges, flyovers, aqueducts, viaducts
- Chimneys, cooling towers and silos
- Walls, ceilings and columns in multi storey car parks

AC 20 is not recommended for areas likely to be subjected to traffic

FEATURES

High resistance to Carbon dioxide (CO₂)

Resistance to fungi & algae growth

Excellent UV resistance

Excellent flexibility & crack bridging properties

Economic and versatile product

PHYSICAL PROPERTIES

AC 20	@ 27 ± 1°C
Density	1.30 g/cc
Solids	55 ± 3%
Application temperature	5°C to 40°C
Touch dry	1 hours
Full cure	7 days
Elongation ASTM D 413	200%
Tensile strength ASTM D413	4 - 5 kg/cm ²
Pull off Strength ASTM D4541	>1 N/mm
Water vapour permeability ASTM E 96	20 gms/m /24 hours
Permeability to CO ₂ EN 1062-6:2002	> 50m
Reduction in chloride ion ingress @28 days	97%
Overcoat Interval	8 - 10hrs

COVERAGE ESTIMATES

Pack Size	Coverage
20 litres	Approximately 3.50 m ² /sq.m @ 200 microns in 2 coats (without dilution)

APPLICATION INSTRUCTIONS

Surface Preparation

The surface to be treated must be dry, clean, structurally sound, and free from oil, grease, wax, polish, laitance, dust and other barrier materials. All holes and cracks must be filled with a suitable filler material such as ACF 8 (acrylic crack filler paste).

Priming

Apply WPM 209 primer using a brush or roller. Allow it to dry for 6 hrs.

Note: WPM 209 should be applied on concrete which is 28 days old.

Application

Add 20% of water to the container of AC 20 and stir well before application. AC 20 may be applied by brush or roller in 2 coats with an overcoat interval of 8 - 10 hrs.

CLEANING

AC 20 can be removed from tools and equipment by using clean water immediately after use. Any hardened material will need to be removed mechanically.

STORAGE AND SHELF LIFE

AC 20 has a shelf life of 18 months if kept in a dry, clean store between 5°C and 30°C in the original unopened containers. The product should be protected from frost, away from direct sunlight and sources of heat.

PRECAUTIONS

During mixing and application the following precautions should be observed: ensure adequate ventilation and avoid contact of the material with the eyes, nasal passages, mouth and unprotected skin. Avoid contact with the hands by wearing protective gloves and by using, if necessary, a suitable barrier cream. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice and after contact with the skin wash immediately with plenty of soap and water. Prolonged contact with the skin should be avoided. Observe personal hygiene, particularly washing the hands after work has been completed or at any interruption whilst work is in progress. Care should be taken when removing gloves to avoid contaminating the insides. In case of accidents seek medical advice.

DISPOSAL/SPILLAGE

Spillage of any product should be absorbed onto sand or other inert materials and transferred to a suitable disposable vessel. Disposal of such spillage or empty packaging should be in accordance with local waste disposal authority regulations.

AC 20

Anti-Carbonation Facade Protective Coating

For further information please refer to the Material Safety Data Sheet.

CONDITIONS OF SALE

Sold subject to the Company's conditions of sale which are available on request.

NOTE

The information supplied in this datasheet is based upon extensive experience and is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products. However, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.



ARDEX ENDURA (INDIA) PRIVATE LIMITED

an ISO 9001:2015 & ISO 14001:2015 certified company
Corporate Office & Regd. Office: Unit No. 406 & 407,
"Brigade Rubix" No. 20, HMT Campus,
Yeshwanthpur Hobli, Bengaluru - 560013.
CIN No: U24233KA1997PTC022383 Tel: +91 80 66746500
Email: customercare@ardexendura.com
Website: www.ardexendura.com

Branches

• AHMEDABAD	+919228019132	• GUWAHATI	+917896002188	• MUMBAI	022 65133299
• AURANGABAD	+918605445577	• HUBBALLI	0836 2970505	• MYSURU	0821 2570171
• BENGALURU	+919972922333	• HYDERABAD	+919703250099	• NAGPUR	+919822223743
• BHUBANESHWAR	0674 2578101	• INDORE	0731 4021148	• PUNE	+919881249292
• CALICUT	0495 2740334	• JAIPUR	0141 2392993	• RAIPUR	0771 4038300
• CHENNAI	044 42805544	• KOLKATA	+919831071084	• SALEM	0427 2211454
• DELHI	+9198106 03431	• LUCKNOW	0522 4043251	• TRIVANDRUM	0471 2598648
• ERNAKULAM	0484 2341044	• LUDHIANA	0161 2532170	• VIJAYAWADA	+918688354587
• GOA	0832 2750992	• MANGALURU	0824 2442176	• VISAKAPATNAM	0891 6469499