



ARDEX AF 148

All Purpose Flooring Adhesive

Dispersion based

Low odour and very low emissions

Extra long open time

Suitable for installation of vinyl sheets, vinyl tiles, LVT and carpet tiles

Semi-wet and pressure sensitive properties



ARDEX GmbH
Postfach 6120 58430 Witten
DEUTSCHLAND
Tel.: +49 (0) 23 02/664-0
Fax: +49 (0) 23 02/664-240
kundendienst@ardex.de
www.ardex.de

ARDEX AF 148

All Purpose Flooring Adhesive

DESCRIPTION

ARDEX AF 148 is a single component, dispersion-based adhesive for laying LVT, PVC and VCT floorings in sheets, tiles, planks and carpet tiles on internal levelled subfloors.

FEATURES & BENEFITS

- Fast: very fast drying time
- Efficient: extremely fast installation of large areas
- Clean: no risk of soiled floor covering
- Versatile application: ideal for roller application
- Can be used as semi-wet and pressure sensitive
- Ease of application with extra long open time
- Universal: extra long tack for carpet tile installation

SURFACE PREPARATION

Subfloors must be level, permanently dry, solid and free from cracks, dirt and adhesion-inhibiting substances.

Apply corresponding ARDEX levelling compounds to achieve a levelled floor.

APPLICATION

Stir ARDEX AF 148 well before using.

Apply evenly on the subfloor with a suitable roller, work from out of the container and avoid adhesive pools.

Fit flooring after corresponding airing time of ARDEX AF 148 and press down firmly.

Remove any air pockets with a cork board or rubbing tool whilst the adhesive is still wet, and roll the floor covering with a 68kg roller and/or a smoothing tool if required.

Roll from side to side first and then end to end. Rolling will ensure good overall contact and minimise the potential for adhesive serration grin through.

NOTE: The specified processing and drying times refer to +20°C and 50% RH. Differing room climate conditions lead to different times.

Do not use ARDEX AF 148 in areas subject to increased moisture, such as entrance areas and wet cells.

COVERAGE

Depending on the surface structure and absorbability

of the subfloor. Approximately 130 - 160g/m² on a flat smooth surface.

TECHNICAL DATA

Raw material base	Dispersion-based
Airing time	approx. 5 - 15 min
Working time	approx. 120 min
Coverage	approx. 130 -160 g/m ²
Cleaning agent	Water, before the adhesive starts to dry
Storage time	12 months at room temperature

PACKAGING

ARDEX AF 148 is packed in a 10 kg plastic pail.

STORAGE

ARDEX AF 148 should not be stored in direct contact with sun and protected from freezing. When stored under the correct conditions and unopened, it has a shelf life of 12 months.

SAFETY PRECAUTIONS

Keep out of reach of children Irritant: Avoid eye and skin contact. Use only in well ventilated areas.

Keep container tightly closed.

In case of contact with eyes and skin, rinse with plenty of water. In event of irritation, seek for medical advice according to the Material Safety Datasheet

DISCLAIMER

The technical datasheets are based on the latest information and given in good faith and represent the best of our knowledge and experience at the time of printing. They are primarily offered for users consideration and evaluation. It is the responsibility of the user to conduct their own tests to validate the suitability of the products. It is also the responsibility of the user to ensure that the products are used and handled correctly and in accordance with any applicable standards, the product instructions and recommendations and only for the uses they are intended. As we have no control over site conditions and the execution of the work, we accept no liability for any loss or damage which may rise as a result thereof. We also reserve the right to update the information at any time without prior notice to you to reflect our ongoing research and development.

ARDEX AF 148

All Purpose Flooring Adhesive

Distributed by Indian offices



ARDEX ENDURA (INDIA) PRIVATE LIMITED
an ISO 9001:2015 & ISO 14001:2015 certified company
Corporate Office & Regd. Office: Unit No. 406 & 407,
"Brigade Rubix" No. 20, HMT Campus,
Yeshwanthpur Hobli, Bengaluru - 560013.
CIN No: U24233KA1997PTC022383 Tel: +91 80 66746500
Email: customercare@ardexendura.com
Website: www.ardexendura.com

Branches

• AHMEDABAD	079 26425310	• HUBBALLI	0836 2970505	• NAGPUR	+919822223743
• AURANGABAD	+918605445577	• HYDERABAD	040 27650293	• PATNA	+919934687909
• BENGALURU:	080 40912934	• INDORE	0731 4021148	• PUNE	+919028811555
• BHUBANESHWAR	0674 2578101	• JAIPUR	0141 2441893	• RAIPUR	0771 4038300
• CALICUT	0495 2740334	• KOLKATA	+919831071084	• SALEM	0427 2271454
• CHENNAI	044 42805544	• LUCKNOW	0522 4043251	• SHIVAMOGGA	+919880605770
• DELHI	011 26384711	• LUDHIANA	0161 2532170	• TRICHY	+919894766109
• ERNAKULAM	0484 2341044	• MANGALURU	0824 2442176	• TRIVANDRUM	0471 2598648
• GOA	0832 2750992	• MUMBAI	022 65133299	• VIJAYAWADA	+918688354587
• GUWAHATI	+917896002188	• MYSURU	0821 2570171	• VISAKAPATNAM	0891 6469499

