



WPM 209

Water Based Emulsion Primer

DESCRIPTION

WPM 209 is used as a primer coat with WPM 309, AC 20 or with any elastomeric acrylic coating system.

FEATURES

- Seals the substrates porosity
- Fills the surface hairline cracks
- Easily applicable by brush or roller
- Unaffected by UV rays
- Enhances bonding with substrate and the topcoat
- Provides deep penetration thus imparts excellent substrate adhesion

PHYSICAL PROPERTIES

| | |
|--------------------------|--|
| WPM 209 | @ 27 ± 1°C |
| Appearance | single component, liquid |
| Colour | Turbid white becomes clear after drying. |
| Specific gravity | 1.01 |
| Viscosity on ford cup B4 | 15 - 20 sec |
| Recoating Period | 1 - 2 Hrs. |

COVERAGE ESTIMATES

| Pack Size | Coverage |
|-----------|---------------------------------------|
| 20 litres | Approx. 8 -10m ² /coat/ltr |

APPLICATION INSTRUCTIONS

Surface Preparation

The surface to be treated must be dry, clean, structurally sound, free from oil, grease, wax, polish, laitance, dust and other barrier materials.

Application

Apply WPM 209 using a brush or roller. Second coat of primer may be required depending on surface porosity and should be applied after 1 - 2 hours interval.

CLEANING

WPM 209 can be removed from tools and equipment by using clean water immediately after use.

STORAGE AND SHELF LIFE

WPM 209 has a shelf life of 24 months if kept in a dry, clean store between 5°C and 30°C in the original unopened containers. The product should be protected from frost, away from direct sunlight and sources of heat.

PRECAUTIONS

WPM 209 is non-hazardous; non-dangerous goods. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin. If contact with eyes, rinse thoroughly with water.

DISPOSAL/SPILLAGE

Spillage of the product should be absorbed onto sand or other inert materials and transferred to a suitable disposable vessel. Disposal of such spillage or empty packaging should be in accordance with local waste disposal authority regulations.

For further information please refer to the Material Safety Data Sheet.

CONDITIONS OF SALE

Sold subject to the Company's conditions of sale which are available on request.

NOTE

The information supplied in this datasheet is based upon extensive experience and is given in good faith in order to help you. Our Company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products. However, as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.

WPM 209

Water Based Emulsion Primer

ARDEX ENDURA (INDIA) PRIVATE LIMITED

an **ISO 9001:2008** certified company
Corporate Office & Regd. Office: Unit No. 406 & 407,
"Brigade Rubix" No. 20, HMT Campus,
Yeshwantpur Hobli, Bengaluru - 560013.
CIN No: U24233KA1997PTC022383 Tel: +91 80 66746500
Email: customercare@ardexendura.com
Website: www.ardexendura.com

Branches

| | | | | | |
|----------------|---------------|-------------|---------------|----------------|---------------|
| • AHMEDABAD | 079 26425310 | • HUBBALLI | 0836 2970505 | • PATNA | +919934687909 |
| • AURANGABAD | +918888480847 | • HYDERABAD | 040 27650293 | • PUNE | 020 64781879 |
| • BENGALURU | 080 40912934 | • INDORE | 0731 4021148 | • RAIPUR | 0771 6539055 |
| • BHUBANESHWAR | 0674 2421901 | • JAIPUR | 0141 2392993 | • SALEM | 0427 2211454 |
| • CALICUT | 0495 2740334 | • KOLKATA | 033 65090604 | • SHIVAMOGGA | +919880605770 |
| • CHENNAI | 044 42805544 | • LUCKNOW | 0522 4043251 | • TRICHY | 0431 6454649 |
| • DELHI | 011 26802949 | • LUDHIANA | 0161 2532170 | • TRIVANDRUM | 0471 2598648 |
| • ERNAKULAM | 0484 2341044 | • MANGALURU | 0824 2442176 | • VIJAYAWADA | +918688354587 |
| • GHAZIABAD | 0120 6541564 | • MUMBAI | 022 65133299 | • VISAKAPATNAM | 0891 6469499 |
| • GOA | 0832 2750992 | • MYSURU | 0821 2570171 | | |
| • GUWAHATI | +917896002188 | • NAGPUR | +919822223743 | | |

